

Vitreous Silica Quartz Tube

Standard Sizes and Electrical Ratings

Vitreous Silica Quartz Tube heaters listed have Type T1 termination.


Quartz Tube Diameter	Overall Length		Heated Length		Watts	Part Number	
	in	mm	in	mm		120V	240V
3/8"	14	355.6	12½	317.5	480	KRD00001	KRD00002
	20	508.0	18½	469.9	720	KRD00003	KRD00004
	26	660.4	24½	622.3	960	KRD00005	KRD00006
	38	965.2	36½	927.1	1450	KRD00007	KRD00008
	48	1219.2	46½	1181.1	1900	—	KRD00009
1/2"	18	457.2	16½	419.1	900	KRD00010	KRD00011
	20	508.0	18½	469.9	900	KRD00012	KRD00013
	26	660.4	24½	622.3	1200	KRD00014	KRD00015
	36	914.4	34½	876.3	1800	KRD00016	KRD00017
	38	965.2	36½	927.1	1800	KRD00018	KRD00019
	42	1066.8	40½	1028.7	1580	KRD00020	KRD00021
	48	1219.2	46½	1181.1	1820	KRD00022	KRD00023
	50	1270.0	48½	1231.9	2400	—	KRD00024
	54	1371.6	52½	1333.5	2060	—	KRD00025
	60	1524.0	58½	1485.9	2300	—	KRD00026
5/8"	24	609.6	21	533.4	1075	KRD00029	KRD00030
	26	660.4	23	584.2	1800	KRD00031	KRD00032
	30	762.0	27	685.8	1375	KRD00033	KRD00034
	38	965.2	35	889.0	2500	—	KRD00035
	42	1066.8	39	990.6	1975	KRD00036	KRD00037
	48	1219.2	45	1143.0	2275	—	KRD00038
	50	1270.0	47	1193.8	3400	—	KRD00039
	54	1371.6	51	1295.4	2575	—	KRD00040
	60	1524.0	57	1447.8	2875	—	KRD00041
	62	1574.8	59	1498.6	4200	—	KRD00042
66	1676.4	63	1600.2	3175	—	KRD00043	
72	1828.8	69	1752.6	3475	—	KRD00044	

Terminations



Type T1 Standard Termination

10-32 thread screw terminal standard termination.



Type T2 Panel Mount Bushings

10-32 thread screw terminals with extension bushings for CRA/TRH housing assemblies.



Type ST Tabs with Slotted Holes

1/2" wide x 3/4" long, with a 9/32" x 3/8" slot. Alternate mounting method.



Type FT Quick Disconnect Fuse Type

Fuse-type connector provides ease of installation. Connectors are 3/8" OD x 1/2" long brass.



Type L1 Straight-Out Leads

10" flexible lead wire externally spliced standard. If longer leads are required, specify.



Type C4 Ceramic Caps with Leads

This termination provides 10-32 screw terminals insulated with ceramic terminal covers. Screws are prewired with 10" flexible lead wire. If longer leads are required, specify (also for T1 or T2).

Ordering Information

Catalog Heaters

Order by Part number for standard heaters listed above.

Part Numbers listed are for heaters supplied with Type 1 Termination. For other terminations a Part Number will be issued at time of order.

Custom Engineered/Manufactured Heaters

Understanding that an electric heater can be very application specific, for sizes and ratings not listed, **TEMPCO** will design and manufacture a Radiant Quartz Heater to meet your requirements.

Standard lead time is 3 weeks.

Please Specify the following:

- Diameter
- Overall Length
- Heated Length
- Wattage
- Voltage
- Termination Type
- Lead Length; if applicable
- Mounting Clamps (See page 7-70)

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

(800) 323-6859 • Email: sales@tempco.com